

LTK-400 Series Optical Sources, Meters and Kits Without Data Storage Capabilities

CORNING

Features and Benefits

High output power and calibrated wavelengths
Easy to use, unparalleled performance

Rugged handheld design
Capable of enduring harsh testing environments

Product warranty and calibration interval
Reduced ownership cost

Packaged as test kits
Test “right out of the box”

The Corning LTK-400 series offers a complete, cost-effective solution for link-loss testing of both multimode and single-mode systems for those users who do not require data storage capabilities. The LTK offers unparalleled performance by combining a source that has one of the highest output powers in the industry with a meter that has 10 calibrated wavelengths from 830 to 1625 nm. The automatic wavelength detection mode allows the power meter to automatically detect/switch to the wavelength being transmitted by the source and has automatic offset nulling under normal temperature and humidity conditions. Both the source and meter have field-interchangeable port adapters and can be powered by standard AA alkaline batteries or by the supplied AC power adapters. The rugged handheld design can withstand the harshest testing environments while the product warranty and recommended three-year calibration interval result in reduced ownership cost.

The LTK-400 series meter and sources are sold individually or packaged as test kits. These test kits include everything needed to test “right out of the box” including the following:

- OS-400 series source and OM-410 meter
- SC and ST® compatible source and meter adapters
- SC and ST compatible jumpers
- SC and ST compatible adapters
- 62.5 and 50 µm test mandrels
- Alkaline batteries and AC power supplies
- Cleaning supplies in a storage case
- Padded carrying case and user’s manual



LTK-400 Series Light Source and Power Meter
| Photo LAN784



LTK-400 Series Test Kit
| Photo LAN786

LTK-400 Series Optical Sources, Meters and Kits Without Data Storage Capabilities



Specifications |

Model Number OM-410 Power Meter*	
Power Meter Port	Ge
Power Range[†]	10 to -60 dBm
Number of Calibrated Wavelengths[‡]	10
Power Uncertainty[§]	± 5 percent ± 1 nW
Resolution^{**}	0.01 dB
Automatic Offset Nulling^{††}	Yes
Warmup Time^{‡‡}	None
Display Units	dB/dBm/W
Automatic Wavelength Recognition^{§§}	Yes
Screen Refresh Rate	3 Hz
Tone Detection	270 Hz, 1 kHz, 2 kHz
Battery Life Typical	300 hours
Warranty and Calibration Interval	3 years
Size (H x W x D)	18.5 x 10.0 x 5.5 cm (7.25 x 4 x 2.125 in)
Weight	0.4 kg (0.9 lb)
Operating Temperature	-10° to +50°C (+14° to +122°F)
Storage Temperature	40° to +70°C (-40° to +158°F)
Relative Humidity	0 to 95 percent, non-condensing

*Specifications are 23°C ± 1°C.

†In CW mode; sensitivity defined as 6 x RMS noise level.

‡Wavelengths: 830, 850, 980, 1300, 1310, 1450, 1490, 1550, 1590 and 1625 nm.

§Traceable to NIST.

**From 10 to -50 dBm.

††Power of > -40 dBm.

‡‡For ± 0.05 dB and temperatures of > 18°C.

§§At 850, 1300, 1310, 1490, 1550 and 1625 nm for power of > -50 dBm.

LTK-400 Series Optical Sources, Meters and Kits Without Data Storage Capabilities



Specifications | (continued)

LTK-400 Series Optical Source*		
Model Number	OS-403D OS-4MDS	OS-404XD OS-4MDS
Central Wavelengths	850 ± 25 nm 1300 -10/+50 nm	1310 ± 20 nm 1550 ± 20 nm
Spectral Width [†]	50 nm (850 nm) 135 nm (1300 nm)	≤ 5 nm (1310 nm) ≤ 5 nm (1550 nm)
Output Power [‡]	≥ -20 dBm (850 nm) ≥ -20 dBm (1300 nm)	≥ 1 dBm (1310 nm) ≥ 1 dBm (1550 nm)
Power Stability [§]	± 0.10 dB	± 0.10 dB
Battery Life ^{**}	120 hours	120 hours
Automatic Wavelength Recognition	Yes	Yes
Tone Detection	270 Hz, 1 kHz, 2 kHz	270 Hz, 1 kHz, 2 kHz
Warranty and Calibration Interval	3 years	3 years
Size (H x W x D)	18.5 x 10.0 x 5.5 cm (7.25 x 4 x 2.125 in)	
Weight	0.4 kg (0.9 lb)	
Operating Temperature	-10° to +50°C (+14° to +122°F)	
Storage Temperature	-40° to +70°C (-40° to +158°F)	
Relative Humidity	0 to 95 percent, non-condensing	
Safety	Class 1M Laser Product	

*Specifications are 23°C ± 1°C.

[†]RMS for lasers and -3 dB width for LEDs; typical values for LEDs.

[‡]LED output power is specified with 62.5 μm fiber. 50 μm coupled power would be lower.

[§]After 15 minutes warm-up; expressed as ± half the difference between the maximum and minimum values during the 8-hour period.

^{**}Typical autonomy in auto mode.

LTK-400 Series Optical Sources, Meters and Kits Without Data Storage Capabilities

CORNING

Ordering Information

Power Meter	
Part Number	Description
OM-410	Optical Power Meter without data storage; SC meter port adapter, ST® compatible meter port adapter, AC adapter, wrist strap, manual and AA alkaline batteries

Light Source	
Part Number	Description
OS-403D	Multimode Optical Source with 850/1300 nm LED; SC source port adapter, ST compatible source port adapter, AC adapter, wrist strap, manual and AA alkaline batteries
OS-404XD	Single-mode Optical Source with 1310/1550 nm laser; SC source port adapter, ST compatible source port adapter, AC adapter, wrist strap, manual and AA alkaline batteries
OS-4MDS	Quad Optical Source with 850/1300 nm LED and 1310/1550 nm laser; two SC source port adapters, ST compatible source port adapter, AC adapter, wrist strap, manual and AA alkaline batteries

Test Kits with Source and Meter	
Part Number	Description
LTK-400MD	Multimode Loss Test Kit including OS-403D source (850/1300 nm LED) and OM-410 meter (no data storage), AA batteries for both units, two AC power supplies, SC and ST compatible jumpers and adapters for MM, manual, SC source port adapter, ST compatible source port adapter, SC meter port adapter, ST compatible meter port adapter, two wrist straps, plastic case of cleaning supplies and padded carrying case
LTK-400SD	Single-Mode Loss Test Kit including OS-404XD source (1310/1550 nm laser) and OM-410 meter (no data storage), AA batteries for both units, two AC power supplies, SC and ST compatible jumpers and adapters for SM, manual, SC source port adapter, ST compatible source port adapter, SC meter port adapter, ST compatible meter port adapter, two wrist straps, plastic case of cleaning supplies and padded carrying case
LTK-4MDS	Quad Multimode and Single-Mode Loss Test Kit including OS-4MDS (850/1300 nm LED) and (1310/1550 nm laser) source and OM-410 meter (no data storage), AA batteries for both units, two AC power supplies, SC and ST compatible jumpers and adapters for both MM and SM, manual, two SC source ports adapter, ST compatible source port adapter, SC meter port adapter, ST compatible meter port adapter, two wrist straps, plastic case of cleaning supplies and padded carrying case

LTK-400 Series Optical Sources, Meters and Kits Without Data Storage Capabilities

CORNING

Accessories

Part Number	Product Description	Units per Delivery	
UI-SC	Test Kit Accessories, Universal Interface Source Connector Adapter, SC	1/1	
UI-ST	Test Kit Accessories, Universal Interface Source Connector Adapter, ST® compatible	1/1	
UI-FC	Test Kit Accessories, Universal Interface Source Connector Adapter, FC	1/1	
OA-SC	Test Kit Accessories, Power Meter Connector Adapter, SC	1/1	
OA-ST	Test Kit Accessories, Power Meter Connector Adapter, ST® compatible	1/1	
OA-FC	Test Kit Accessories, Power Meter Connector Adapter, FC	1/1	
OA-LC	Test Kit Accessories, Power Meter Connector Adapter, LC	1/1	
OA-MTRJ	Test Kit Accessories, Power Meter Connector Adapter, MT-RJ	1/1	
PS-9-1	Test Kit Accessories, AC Power Adapter for 400 series source or meter	1/1	
CASE-HH-400	Test Kit Accessories, Hard-Shell Transit Case for two 400 series instruments and accessories (17.25 x 11.25 x 7 in; 8 lb)	1/1	
CASE-STD-400	Test Kit Accessories, Padded Carrying Case for two 400 series instruments and accessories	1/1	
OTS-COMBOMAN	Test Kit Accessories, Set of Mandrels for 50 and 62.5 µm multimode fiber	1/1	

* Note: Other test jumper kits (TJK) configurations are available. Please contact a Corning Customer Care Representative for more information.

Corning Optical Communications LLC • PO Box 489 • Hickory, NC 28603-0489 USA

800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. Corning Optical Communications is ISO 9001 certified. © 2014 Corning Optical Communications. All rights reserved.