

Fujikura CT-100B Specs
Provided by www.AAATesters.com

HIGH PRECISION FIBER CLEAVER

CT-103/104/107
CT-03/04/07

The Very Best for Single and Mass Fiber Cleavings



Specifications Other than a complete cleaver, just an adapter plate or a cleaver base is also available.

(1) Complete High Precision Fiber Cleaver

Cleaver Model No. (Adapter Plate and Cleaver Base)	Conventional Complete Cleaver			Enhanced Complete Cleaver		
Adapter Plate Model No.	CT-03	CT-04	CT-07	CT-103	CT-104	CT-107
Cleaver Base Model No.	AD-03	AD-04	AD-07	AD-03	AD-04	AD-07
	CT-04B			CT-100B		

(2) Adapter Plate only


Adapter Plate Model No.	AD-03	AD-04	AD-07		AD-03	AD-04	AD-07	
			Guide A	Guide B			Guide A	Guide B
Cleaved Length (mm)	16	6-16	6-20	10-20	16	6-16	6-20	10-20
Fiber Coating Diameter (mm)	0.25-0.9	0.25	0.25	0.9	0.25-0.9	0.25	0.25	0.9
Cladding Diameter (microns)	125	125	125	125	125	125	125	125

(3) Cleaver Base only

Cleaver Base Model No.	Conventional Base		Enhanced Base	
	CT-04B		CT-100B	
Applicable Fiber Cladding Material	Conventional silica		Titanium (Ti) doped silica as well as conventional silica	
No. of Scriber Blade's Height Positions	1 Only one for silica cladding		2 (Switchable) "T" and "S" positions for Ti doped silica and conventional silica claddings respectively	
No. of Scriber Blade's Rotational Positions	12		12	
No. of Cleavings per Position	1,000		1,000	
Total No. of Cleavings per Blade	12,000		12,000	
Anvil Movement	Tilte		Ideal linear up and down	
No. of Fibers to be Cleaved (ditto but for use with mass fiber fusion splicer)	1 with AD-03, AD-04 or AD-07 (1-12 when used with optional respective Fiber Holders hereafter)		1 with AD-03, AD-04 or AD-07 (1-12 when used with optional respective Fiber Holders hereafter)	
Dimensions(mm/inch)	90×55×55 / 3.5×2.2×2.2		90×55×55 / 3.5×2.2×2.2	
Weight(kg/lb)	0.5 / 1.1		0.5 / 1.1	

Fiber Holder for Cleaving as Well as Stripping and Splicing Used with Mass Fiber Fusion Splicer

Fiber Holder for Encapsulated Fiber Ribbons



Fiber Holder Model	FH-2	FH-4	FH-6	FH-8	FH-10
Fiber Count	2	4	6	8	10
Cleaved Length (mm)	10				

Fiber Holder for Both Edge-Bonded Fiber Ribbons and Bundle Fibers



Fiber Holder Model	FH-2	FH-4	FH-6	FH-8	FH-10	FH-12
Fiber Count	2	4	6	8	10	12
Cleaved Length (mm)	10					

*Except for the model FH-900, all the other models are designed for 250µm OD UV cured acrylate coated fibers irrespective of the configuration.

Fiber Holder for Single 250µm OD Fiber



Fiber Holder Model	FH-250
Fiber Count	1
Cleaved Length (mm)	10

Fiber Holder for Single 900µm OD Fiber



Fiber Holder Model	FH-900*
Fiber Count	1
Cleaved Length (mm)	10

Specifications subject to change without prior notice.

Fujikura Ltd.

Fujikura Europe Ltd.

Alcoa Fujikura Ltd. Telecommunications Division

Fujikura Asia Ltd.

1-5-1, Kiba, Koto-ku, Tokyo 135-8512, Japan
Phone : 03-5606-1164 Fax : 03-5606-1534 <http://www.fujikura.co.jp>

C51 Barwell Business Park, Leatherhead Road, Chessington, Surrey KT9 2NY, UK
Phone : +44(181)240-2000 Fax : +44(181)240-2010 <http://www.fujikura.co.uk>

150, Ridgeview Circle, Duncan, SC29334, USA
Phone : 1-800-AFL-FIBER Fax : 864-433-5353 <http://www.afl-link.com>

460 Alexandra Road #22-02 PSA Bldg., Singapore 119963
Tel : +65 278-8955 Fax : +65 273-7705 <http://www.fujikura.com.sg>