

Riser Bond Model 6000

MULTI-FUNCTION TELEPHONE NETWORK ANALYZER



FEATURES/KEY BENEFITS

- **Diagnostic and fault location functions in one instrument** – Integrated testing system enables the technician to diagnose and locate faults with one easy to use, high quality instrument.
- **Diagnostic Test Package**- Identify conditions on the line that can adversely affect service using the following diagnostic tools:
 - Multi-Meter** – Measure AC volts, DC volts, foreign battery, resistance and insulation resistance.
 - Pair Quality Tests** – Measure loop current, noise metallic, power influence and longitudinal balance.
- **Fault Location Test Package** - Restore existing service quicker or reclaim unused lines for new service with accurate fault location tools:
 - Time Domain Reflectometer (TDR)** – Accurately locate opens, shorts, water in cable, bad splices and cable damage with the same full-function TDR found in Riser Bond's stand-alone instruments.
 - Resistance Fault Locator (RFL)** – Three test modes. Locate resistance faults on a pair or on a single conductor.
 - Stress TDR** – This exclusive feature enhances the instrument's ability to locate faults due to moisture in the cable.
 - Open/Capacitance Meter** – Measure capacitance to the end of the pair or locate fault caused by an open circuit.
- **Ease-of-Use Features** – The soft-key menu's intuitive left-to-right operation guides the technician through logical testing steps to diagnose and locate faults. Most tests are performed using the same connection to the line.
- **Auto-Test and Fault Analysis Functions** – Press the Auto-Test key to perform a series of basic diagnostic tests. The Fault Analysis function will then suggest the appropriate fault location tool to use to most effectively locate the problem.
- **SUPER-STORE Waveform Data Storage** – Analyze TDR waveforms in a more convenient time or place. The instrument also stores Auto-Test records.
- **WAVE-VIEW Software** – View, manipulate, print and archive TDR waveforms on your computer. Document plant, certify new builds, and store waveforms for later comparisons.
- **Optional Oscillator and Probe** – One unassisted technician working at a distance from the exchange can disconnect a customer's service, identify the cable pair, open and close the circuit, and reconnect the customer after desired tests are complete.
- **Large LCD Display** – Test results and interpretive information are presented in an easy to read format on a screen that is larger than those found on many competitive units.

PRODUCT SPECIFICATIONS

PHYSICAL DIMENSIONS	
Main instrument without carrying case & accessories	
Width:	10.71 inches (272mm)
Height:	6.93 inches (176mm)
Depth:	3.15 inches (80mm)
Weight:	4.8 pounds (2.2kg)
Main instrument with carrying case & accessories	
Width:	11.18 inches (284mm)
Height:	7.80 inches (198mm)
Depth:	7.0 inches (178mm)
Weight:	7.9 pounds (3.6kg)
POWER	
Internal:	Rechargeable, 7.2V Nickel metal hydride battery pack
External:	12VAC or VDC, 1250mA power supply
Operating Time:	Greater than 5 hours, continuous without backlight
ENVIRONMENT	
Operating temperature:	0°C (+32°F) to +50°C (+122°F)
Storage temperature:	-20°C (-4°F) to +60°C (+140°F)
Humidity:	95% maximum relative humidity, non-condensing
	IEC 68-2-3
Vibration:	IEC 68-2-6
Shock (Bump):	IEC 68-2-29, 40g, 6ms,1000 shocks in each axis
Drop:	IEC 68-2-27, 1m free fall, packaged in carry case
Moisture rating:	IP54
DISPLAY	
320 x 240 dot-matrix, liquid crystal display (LCD) with CCFL backlighting	
MULTI-METER	
DC Voltage:	0 to 400V
Resolution:	0.1V
Accuracy:	1% ±0.1V
AC Voltage:	0 to 400V
Resolution:	0.1V
Accuracy:	2% ±0.1V
Foreign Battery:	2 to 400V
Resolution:	0.1V
Accuracy:	1% ±0.1V
Resistance:	0 to 1999.9Ω
Resolution:	0.1Ω
Accuracy:	0.2% ±0.2Ω
	2kΩ to 10kΩ
Resolution:	1Ω
Accuracy:	0.2% ±1Ω

INSULATION RESISTANCE	
Voltages:	50V/100V/250V/500V
0Ω to 9.99MΩ	
Resolution:	0.01MΩ
Accuracy:	2% ±0.01MΩ
10MΩ to 99.9MΩ	
Resolution:	0.1MΩ
Accuracy:	4%
100MΩ to 999MΩ	
Resolution:	1MΩ
Accuracy:	10%
OPEN/CAPACITANCE METER	
0 to 1000ft (0 to 305m)	
Resolution:	1ft (0.3m)
Accuracy:	2% ±3ft (1m)
1000ft to 10,000ft (305m to 3,050m)	
Resolution:	10ft (3m)
Accuracy:	±3%
10,000ft to 100,000ft (3,050m to 30,500m)	
Resolution:	100ft (30m)
Accuracy:	±5%
100,000ft to 150,000ft (30,500m to 45,700m)	
Resolution:	1000ft (300m)
Accuracy:	±8%
0 to 9.99nF	
Resolution:	0.01nF
Accuracy:	2% ± 0.06nF
10.0 to 99.9nF	
Resolution:	0.1nF
Accuracy:	±3%
100 to 999nF	
Resolution:	1nF
Accuracy:	±5%
1000 to 2000nF	
Resolution:	1nF
Accuracy:	±8%
PAIR QUALITY	
Loop Current:	0 to 120mA
Resolution:	0.1mA
Accuracy:	5% ±0.2mA
Noise Metallic:	0 to 50dBmC
Resolution:	1dB
Accuracy:	±2dB
Power Influence:	40 to 100dBmC
Resolution:	1dB
Accuracy:	±2dB
Longitudinal Balance:	40 to 62dB
Resolution:	1dB
Accuracy:	±2dB

TIME DOMAIN REFLECTOMETER (TDR)

Loaded and non-loaded cable

Maximum Ranges:

Live waveform:

63,700 feet (19,400 meters) at 99.0% VOP

38,600 feet (11,700 meters) at 60.0% VOP

Range varies with VOP. Maximum testable cable length varies with pulse width and cable type.

Stored waveform:

11,900ft (3,600.0m) at 99.0% VOP

7,200ft (2,200.0m) at 60.0% VOP

Range varies with VOP.

Horizontal Resolution:

Up to 2,000ft (610m): <0.25ft (0.07m) at 99.0% VOP

<0.07ft (0.02m) at 30.0% VOP

Over 2,000ft (610m) 1ft. (0.3m) at any VOP

Vertical Resolution:

14 bits with 137 dots displayed

Vertical Sensitivity:

Greater than 65dB

Output Signal:

Pulse widths of 2ns, 25ns, 100ns, 500ns, 1.5µs, 4.4µs and 330µs

Output Balance:

Variable, from 80Ω to 120Ω

Velocity of Propagation:

Two user-selectable display formats:

VOP (%): Non-loaded cable: 30.0% to 99.0%

Loaded cable: 0.8% to 20.0%

V/2: Non-loaded cable: 147.5 to 486.9ft/µs
(45.0 to 148.4m/µs)

Loaded cable: 3.9 to 98.4ft/µs
(1.2 to 30.0m/µs)

Input Protection:

400 VAC or VDC up to 60Hz

Distance Accuracy:

Accuracy will vary with cable VOP and cable type: ±0.5ft (0.15m) plus ±0.1% of reading

SOFTWARE NOISE FILTERS

Automatic/Manual Noise Filter: Multi-function/Multi-level filtering

RESISTANCE FAULT LOCATOR (RFL)

Location Range:

0 to 150kft (0 to 45km)

Resistance fault range:

0 to 50MΩ

Accuracy:

3-Wire Test: ±0.25% of DTS plus ±0.4Ω

4-Wire Test: ±0.25% of DTS plus ±0.25Ω

Kupfmuller Test: ±1.0% of DTS plus ±1Ω

Waveform Storage

All with full vertical resolution: 32 waveforms

RISER BOND OSCILLATOR AND PROBE

Communications for: short pair, open pair, exchange connect, disconnect, pair identification tone.

ACCESSORIES:

Standard: Operator's Manual, 12VDC charger, nylon carry/ accessory bag, shoulder strap, 2 sets telco connection leads plus ground lead, pair shorting strap, VOP card.

Technological advances allow changes in specifications and/or components
Changes may be made without notification.



Radiodetection (USA) 28 Tower Road, Raymond, Maine 04071, USA

Tel: +1 (207) 655 8525 Toll Free: +1 (877) 247 3797 Fax: +1 (207) 655 8535 rd.sales.us@spx.com www.radiodetection.com

Radiodetection Ltd. (UK) Western Drive, Bristol BS14 0AF, UK

Tel: +44 (0) 117 976 7776 Fax: +44 (0) 117 976 7775 rd.sales.uk@spx.com www.radiodetection.com