

ELS-100

Light Source

EPM-100

Power Meter

NETWORK TESTING—OPTICAL

[EXFO EPM-100 Specs](#)

Provided by www.AAATesters.com



- Cost-effective, rugged handheld instruments designed for reliable performance
- Easy-to-use interface for error-free testing
- Interchangeable connectors, for first-class flexibility
- Particularly suited to the testing and troubleshooting of LAN/WAN fiber-optic networks

Introducing EXFO's FiberBasix testers, a series of handheld instruments designed to meet your basic day-to-day test requirements, while helping you stay within budget. These worry-free, straightforward solutions provide the tools you need to accurately measure signal attenuation during fiber-optic cable installation.

The FiberBasix 100 Series includes two highly convenient instruments:

- The **ELS-100 Light Source**, combines four wavelengths for singlemode and multimode testing
- The **EPM-100 Power Meter**, which offers high accuracy and referencing capabilities



ELS-100 Light Source: Multiwavelength Capability

EXFO's ELS-100 Light Source provides excellent stability and high measurement accuracy. Its configuration includes two singlemode wavelengths (1310 and 1550 nm) and two multimode wavelengths (850 and 1300 nm) for maximum versatility. For testing all fiber types. It is the perfect complement to the FiberBasix EPM-100 Power Meter when it comes to measuring attenuation on fiber-optic links.



■ The ELS-100 Light Source

EPM-100 Power Meter: High Accuracy and Easy Referencing

The EPM-100 Power Meter provides highly accurate power measurements, as well as reference value setting capabilities. What's more, this convenient unit requires no offset nulling, and it offers power autonomy of 300 hours, for reliable, long-lasting performance in the field.



■ The EPM-100 Power Meter

ELS-100 SPECIFICATIONS ^a

| Model ^b | 23BL | 12D |
|---|-----------|---------------------------|
| Central wavelength (nm) | 1310 ± 20 | 850 ± 25 |
| | 1550 ± 20 | 1300 +50/-10 |
| Spectral width ^c (nm) | ≤ 5 | 50/135 |
| Output power (dBm) | ≥ 1/≥ 1 | ≥ -20/≥ -20 (62.5/125 μm) |
| Power stability ^d (dB) | | |
| 8 hours | ± 0.10 | ± 0.10 |
| Battery life (hours) (typical) | 50 | 55 |
| Warranty and recommended calibration interval (years) | 1 | 1 |

EPM-100 SPECIFICATIONS ^a

| Model ^e | EPM-102 |
|---|-------------------|
| Power meter port | Ge |
| Power range ^f (dBm) | 10 to -60 |
| Range displayed (dBm) | Down to -65 |
| Number of calibrated wavelengths ^g | 6 |
| Power uncertainty ^h | ±5 % ± 1 nW |
| Resolution (dB) | 0.01 ⁱ |
| Automatic offset nulling | Yes |
| Warm-up time ^f (s) | 0 |
| Display units | dB/dBm/W |
| Screen refresh rate (Hz) | 3 |
| Battery life (hours) (typical) | > 300 |
| Warranty and recommended calibration interval (years) | 1 |

Notes

- a. Guaranteed unless otherwise specified.
- b. All specifications valid at 23 °C ± 1 °C, with an FC connector.
- c. rms for lasers and FWHM for LEDs; typical values for LEDs.
- d. After 15 minutes warm-up; expressed as ± half the difference between the maximum and minimum values measured during the period, with an APC connector on the power meter.
- e. All specifications valid at 1550 nm and 23 °C ± 1 °C, with an FC connector.
- f. In CW mode, sensitivity defined as 6x rms noise level.
- g. Wavelengths: 850 nm, 1300 nm, 1310 nm, 1490 nm, 1550 nm and 1625 nm.
- h. Traceable to national standards.
- i. From 10 dBm to -50 dBm.

GENERAL SPECIFICATIONS

| | | |
|-------------------|----------------------------|--|
| Size (H x W x D) | 185 mm x 100 mm x 55 mm | (7 ¹ / ₄ in x 4 in x 2 ¹ / ₈ in) |
| Weight | 0.4 kg | (0.9 lb) |
| Temperature | | |
| operating | -10 °C to 50 °C | (14 °F to 122 °F) |
| storage | -40 °C to 70 °C | (-40 °F to 158 °F) |
| Relative humidity | 0 % to 95 % non-condensing | |

STANDARD ACCESSORIES

User guide, Certificate of Calibration, instrument stickers in four languages, AC adapter, EUI-XX (ELS), connector adapter (FOA-XX) (EPM), three AA batteries, wrist strap.

SAFETY

21 CFR 1040.10 and IEC 60825-1:1993+A1:1997+A2:2001:
ELS-500: CLASS 1 LASER PRODUCT

ORDERING INFORMATION

ELS-100-XX-XX

■ **Model**

ELS-100-12D-23BL = 850/1300 nm LED (62.5/125 mm), 1310/1550 nm laser (9/125 mm)

Example: ELS-100-12D-23BL-EI-EUI-89

■ **Connector ^a**

- EI-EUI-89 = UPC/FC narrow key ^b
- EI-EUI-90 = UPC/ST ^b
- EI-EUI-91 = UPC/SC ^b
- EI-EUI-95 = UPC/E-2000 ^b

EPM-10X-XX

■ **Model**

EPM-102 = Ge detector

Example: EPM-102-FOA-22

■ **Connector Adapter ^a**

- FOA-22 = FC (PC/SPC/UPC/APC), NEC-D3
- FOA-32 = ST (PC/SPC/UPC)
- FOA-54 = SC
- FOA-96B = E-2000
- FOA-98 = LC

TEST KIT ORDERING INFORMATION

FBK-103-XX Contractor Test Kit

- EPM-102-XX Power Meter, Ge detector
- ELS-100-12D-23BL-XX Light Source, 850/1300 nm LED and 1310/1550 nm laser (2 ports)
- One TJ-BXX-XX test jumper
- One TJ-DXX-XX test jumper
- Carrying case GP-10-061

Notes

- a. Other connectors and connector adapters available. Consult our website at www.EXFO.com/accessories for details.
- b. Interchangeable connection.

EXFO Corporate Headquarters > 400 Godin Avenue, Quebec City (Quebec) G1M 2K2 CANADA | Tel.: +1 418 683-0211 | Fax: +1 418 683-2170 | info@EXFO.com

Toll-free: +1 800 663-3936 (USA and Canada) | www.EXFO.com

| | | | | |
|-------------------------------|--|--|---------------------------|-------------------------|
| EXFO America | 3701 Plano Parkway, Suite 160 | Plano, TX 75075 USA | Tel.: +1 800 663-3936 | Fax: +1 972 836-0164 |
| EXFO Asia | 100 Beach Road, #22-01/03 Shaw Tower | SINGAPORE 189702 | Tel.: +65 6333 8241 | Fax: +65 6333 8242 |
| EXFO China | 36 North, 3 rd Ring Road East, Dongcheng District Room 1207, Tower C, Global Trade Center | Beijing 100013 P. R. CHINA | Tel.: + 86 10 5825 7755 | Fax: +86 10 5825 7722 |
| EXFO Europe | Omega Enterprise Park, Electron Way | Chandlers Ford, Hampshire S053 4SE ENGLAND | Tel.: +44 2380 246810 | Fax: +44 2380 246801 |
| EXFO NetHawk | Elektroniikkatie 2 | FI-90590 Oulu, FINLAND | Tel.: +358 (0)403 010 300 | Fax: +358 (0)8 564 5203 |
| EXFO Service Assurance | 270 Billerica Road | Chelmsford, MA 01824 USA | Tel.: +1 978 367-5600 | Fax: +1 978 367-5700 |

EXFO is certified ISO 9001 and attests to the quality of these products. This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. EXFO has made every effort to ensure that the information contained in this specification sheet is accurate. However, we accept no responsibility for any errors or omissions, and we reserve the right to modify design, characteristics and products at any time without obligation. Units of measurement in this document conform to SI standards and practices. In addition, all of EXFO's manufactured products are compliant with the European Union's WEEE directive. For more information, please visit www.EXFO.com/recycle. Contact EXFO for prices and availability or to obtain the phone number of your local EXFO distributor.

For the most recent version of this spec sheet, please go to the EXFO website at <http://www.EXFO.com/specs>

In case of discrepancy, the Web version takes precedence over any printed literature.