



## LANTEK® 7 LAN Cable Certifier

The LANTEK 7 display unit comes with the brightest 1/4 VGA color screen in the industry. The remote unit has a two-line black and white LCD display to enhance communications, and can initiate an Auto Test to increase productivity in one-person operations. Both units have an overmolded edge to function in the harshest environments.

Along with serial and USB ports, LANTEK 7 comes standard with two full-function PCM/CIA slots to accept compact flash memory and provide for future capabilities. This allows for virtually unlimited test storage with graphs keeping your unit in the field. LANTEK 7 comes with LANTEK Reporter PC software that can upload stored tests from the serial or USB ports, or compact flash memory and can create brief, summary, or detailed certification reports for your clients.

Don't limit yourself to Category 6/ISO E. LANTEK 7 allows you to certify the most advanced installations.

| LANTEK 7                       | Range             | Resolution    | Accuracy                   |
|--------------------------------|-------------------|---------------|----------------------------|
| Length (50-100 $\Omega$ cable) | 0 - 2000 ft.      | 1 ft.         | $\pm(3\% + 3 \text{ ft.})$ |
| Delay                          | 0 - 8000 ns       | 1 ns          | $\pm(3\% + 1 \text{ ns})$  |
| Average Impedance              | 35 - 180 $\Omega$ | 0.1 $\Omega$  | $\pm(3\% + 1 \Omega)$      |
| Capacitance (Bulk)             | 0 - 100 nF        | 1 pF or 3 dig | $\pm(2\% + 20 \text{ pF})$ |
| Capacitance                    | 0 - 100 pF/ft.    | 0.1 pF        | $\pm(2\% + 1 \text{ pF})$  |
| DC Loop Resistance             | 0 - 200 $\Omega$  | 0.1 $\Omega$  | $\pm(1\% + 2 \Omega)$      |
| Attenuation                    | 1-750 MHz         | 0.1 dB        | Level III*                 |
| NEXT                           | 1-750 MHz         | 0.1 dB        | Level III*                 |
| Return Loss                    | 1-750 MHz         | 0.1 dB        | Level III*                 |
| ELFEXT                         | 1-750 MHz         | 0.1 dB        | Level III*                 |
| Noise Floor                    | < -90 dB          |               |                            |
| Dynamic Range                  | > 90 dB           |               |                            |

\* Level III only specified to 250 MHz

| Autotest Storage Capacity (Internal Memory)*      |                                                                                                                           |
|---------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------|
| No Graphics                                       | Up to 6,000 Tests                                                                                                         |
| With Graphics                                     | Up to 100 Tests                                                                                                           |
| Autotest Storage Capacity (External 32 MB Flash)* |                                                                                                                           |
| No Graphics                                       | Up to 24,000 Tests                                                                                                        |
| With Graphics                                     | Up to 400 Tests with 32 MB                                                                                                |
| * Depending on Autotest Categories                | Up to 3,200 Tests with 256 MB                                                                                             |
| Autotest time (250 MHz)                           | Approx. 25 seconds                                                                                                        |
| Autotest time (600 MHz)                           | Approx. 35 seconds                                                                                                        |
| Standard Test Compliance                          | ANSI/TIA/EIA 568B, Category 6 (Draft), ISO C/D and ISO E/F (draft), AS/NZS 3080, IEEE 802.3 Ethernet, EN50173, EN50173.A1 |
| Cable Types                                       | UTP/ScTP/FTP<br>CAT 3/5e/6/7; ISO C/D/E/F (Channel, Basic, and Permanent Link)<br>IBM STP Type 1,2,6, Coax                |
| Dimensions                                        | 10.1" x 5.0" x 2.3" Display & Remote<br>256mm x 127mm x 58mm Display & Remote                                             |
| Weight                                            | 2.3 lb (1050g) - Display<br>2.0 lb (914g) - Remote<br>1.2 lb (548g) - Battery                                             |
| Battery Packs                                     | NIMH (rechargeable)                                                                                                       |
| Typical Operating Life (Battery)                  | 8 hrs                                                                                                                     |
| Max. Operating Temp.                              | 0°C - 50°C                                                                                                                |
| Max. Storage Temp.                                | - 20°C to + 70°C                                                                                                          |
| Humidity                                          | 5-90 % noncondensing                                                                                                      |

LANTEK 7 comes standard with all the items necessary to certify your job and create certification reports:

|                                                             | LANTEK 7 | LANTEK 7P |
|-------------------------------------------------------------|----------|-----------|
| Soft Carry Case                                             | ✓        |           |
| Display unit with battery                                   | ✓        | ✓         |
| Remote unit with battery                                    | ✓        | ✓         |
| LANTEK Reporter Software                                    | ✓        | ✓         |
| Serial and USB cables                                       | ✓        | ✓         |
| Two AC wall adapters                                        | ✓        | ✓         |
| Two talksets                                                | ✓        | ✓         |
| User manual                                                 | ✓        | ✓         |
| Quick Start Guide                                           | ✓        | ✓         |
| Registration Card                                           | ✓        | ✓         |
| <b>Included are the following adapters and Patch cords:</b> |          |           |
| Two Category 7 channel adapters                             | ✓        | ✓         |
| Two Category 7 Reference Patch cords                        | ✓        | ✓         |
| Two Category 7 to Category 6 Reference Patch cords          | ✓        | ✓         |
| <b>Premium Package:</b>                                     |          |           |
| Hard carry case                                             |          | ✓         |
| PCM/CIA adapter                                             |          | ✓         |
| 32 MB compact flash                                         |          | ✓         |
| USB port flash reader for PC                                |          | ✓         |
| Offline battery charger                                     |          | ✓         |

*Field calibration does not require a special adapter. It is accomplished through connecting a patch cord between the channel adapters.*

### IDEAL INDUSTRIES, INC.

9145 Balboa Av., San Diego, CA 92123 U.S.A.

Tel: (858) 279-2955

Fax: (858) 278-5141

Becker Place, Sycamore, IL 60178 U.S.A.

Toll-Free: (800) 435-0705 in U.S.A.

Becker Place: (815) 895-5181

Ajax, Ontario, L1S 2E1, Canada.

Toll-Free: (800) 527-9105 in Canada.

Canada: (905) 683-3400

### IDEAL INDUSTRIES (U.K.) LTD.

225 Europa Boulevard, Gemini Business Park, Warrington

Cheshire WA5 7TN, England

Tel: 44-1925-444446

Fax: +44-1925-445501

### IDEAL INDUSTRIES GmbH.

Gutenbergstrasse 10, 85737 Ismaning, Germany.

Tel: +49-89-99686-0

Fax: +49-89-99686-111

[www.idealindustries.com](http://www.idealindustries.com)