

Core Alignment Fusion Splicer

Single Optical Fiber Fusion Splicer

PCT/KR2008/003533

Swift-S3



Features

- Core Alignment by IPAS Technology
- Resistance to the Environment with Shock, Rain and Dust
- Powerful Battery with Large Capacity
- Dual Sleeve Heater
- Automatic Execution of Discharge Calibration
- Smallest, Lightest & Fastest
- 4.3" Color LCD Monitor with Touch Panel
- Bidirectional Operation System
- Attached Sleeve Loader
- Attached Night Light
- ROHS Compliant

Benefits and Features

Swift-S3



IPAS Technology basis Core Alignment

Swift-S3 is the core alignment splicer based on IPAS (Image Pattern Analysis Alignment System) Technology

Smallest, Lightest and Fastest

This splicer is the smallest, lightest and fastest among all the existing core alignment splicers

Dimension : 138(W) × 160(L) × 135(H)

Weight : 2.3kg

Splicing Time : 9 seconds,

Tube heat : 26 seconds

} Battery and shock
proof rubbers are
included



Resistance to the Environment with Dust, Shock and Rain

The splicer with high reliability has stable performance even in a harsh environment



Powerful Lithium Polymer Battery with Large Capacity

Performs 250 cycles of fusion splicing and sleeve heating with the standard battery



Automatic Execution of Discharge Calibration

Detects the surrounding environment of temperature, humidity, air pressure and others by itself and measures discharge calibration rate automatically

Swift-S3

Benefits and Features

4.3-inch Color LCD Monitor with Touch Pannel

Magnification : 300X, 170X

For user's convenience, LCD monitor has been designed with touch panel in addition to the operation switch

Bidirectional Operation System

For user's ergonomic preference, the screen can be turned around for one's chosen viewing direction as the monitor can be flipped upward and downward


Equipped with Sleeve Loader to Prevent Contamination and Provide Convenience

While working in a man hole, the loader prevents the supplementary sleeve from falling and being contaminated with a flowing water.

Working in aerial space such as telephone pole, the loader also prevents the supplementary sleeve from falling down.

Built-in Dual Sleeve Heaters

By using the dual sleeve heaters, a user can continuously without interruption and improves one's productivity by 20%



STANDARD PACKAGE & OPTIONAL



Cleaver Options



CI-01



CI-02



CI-03A



CI-03B

SPECIFICATIONS

Subject	Description
Alignment	IPAS Core to Core Alignment (Image Pattern Analysis Alignment System)
Applicable fibers	SMF(ITU-T G.652), MMF(ITU-T G.651), DSF(ITU-T G.653), NZDSF(ITU-T G.655), EDFA, EI980, Splicing available with different type fiber(SM/MM), ITU-T G.657
Fiber Diameter	cladding : 80 μ m ~ 150 μ m, coating : 100 μ m ~ 1000 μ m (single)
Fiber cleave length	250 μ m (Coat) : 8 ~ 16mm, 900 μ m : 16mm
Typical splice loss	SMF : 0.02dB, MMF : 0.01dB, DSF : 0.04dB, NZDSF : 0.04dB
Return loss	Less then -60dB
SPLICE Time	SPLICE : Typical 9sec, Tube Heat : Typical 26sec with S-160(60mm) Tube
Program	SPLICE Mode : 100, Heat Mode : 50
Storage of splice result	the last 2,000 results (Image 100 results)
Operating altitude	0 ~ 5000m above sea level
Operating condition	-10℃ to 50℃, humidity : 95%, non-Condensing
Storage condition	-40℃ to 80℃, 0 to 95% RH
Protection	Wind 15 $\frac{m}{s}$, shock proof, water proof, dust proof
SIZE, Weight	138W × 160L × 135H (include Monitor & Rubber), 2.3Kg (include Battery)
Terminal	USB, RCA, External Power
Power	DC 14.8V Battery (5600mAh), 100 ~ 240V AC Adapter
Additional power	DC 12V automobile power outlet available
No of splice/Heating with Battery	250cycle, lithium polymer batteries
Electrode	more than 2,000 times splicing without exchange
Mechanical proof test	2N / 4.4N (OPTION)
Display	Two CMOS cameras and 4.3" color LCD monitor, with touch panel
Fiber view and magnification	X/Y 300X, 170X


STANDARD PACKAGE

Description	Model	Q'ty
Arc Fusion Splicer	S3	1
AC Adapter	S311	1
Sleeve Loader	S312	2
Spare Electrodes	EI-21	1
Battery Pack	S313	1
Alcohol dispenser		1
Carrying Case		1
User Manual		1

OPTION

Description	Model
Battery Pack	S313
Fiber Cleave	CI-01, CI-02, CI-03, CI-03B
Heating Stripper	Auto Stripper(ATS)
Fiber Solution	Multipack(MP-S)
Protection Sleeves	S-160(60mm), S-140(40mm)
Cleave Blade	BI-05

Headquarter : #703 Gwanpyung-dong Yusung-gu Daejeon, Korea
 (Korea) Tel : +82 42 671 5609 Fax : +82 42 671 5612
 America branch : 4230 LBJ Freeway Suite 235C Dallas Texas 75244, USA
 (Dallas) Tel : +1 972 556 0916 Fax : +1 972 910 8384
 Europe branch : Ludwig-Erhard str, 30-34 65760 Eschborn, Deutschland
 (Germany) Tel : +49 1522 3689 747
 India branch : A-26/4 Mohan Cooperative Estate Mathura Road Delhi, India
 (Delhi) Tel : +91 11 4055 5954, +91 11 4056 7229
 China branch : E3-8F Juneyao International Plaza NO789 Zhaojiabang Rd,
 (Shanghai) Shanghai 200032, China
 Tel : +86 21 5836 0950, +86 21 5836 0189 Fax : +86 21 5836 0951
 Russia branch : ya ul, Entuziastov 3 111024 Moscow, Russian Federation,
 (Moscow) Tel : +7 926 233-1605



ILSINTECH Co., Ltd. www.ilsintech.com