# INNO V8 Specs Provided by www.AAATesters.com



- Fully automated high precision cleaving for ribbon fiber cable as well as 250µm, 900µm, 3.0mm and flat cable with universal holder.
- Durable blade lifespan over 48,000 fiber cleaves.



## Full Automatic Single & Ribbon Fiber Cleaver

Compatible with all VIEW series fusion splicer Available for single and ribbon cleaving up to 12 fibers Automatic 1 step operation Built-in automatic fiber shard collector

### Description

# V8 Automatic High Precision Cleaver is an istrument for high precision fiber cutting. V8 can be installed with a variety of holders for ribbon cable up to 12 fibers as well as universal holder which is applicable to 250µm, 900µm, 3.0mm fiber cable and flat cable. Work efficiency can be maximized with a simple 1 step operation and automatic collector for fiber shards and off cuts. The blade provides over 48,000 fiber cleaves by easy and simple blade position selection. Helped by unmatched functionalities, users can achieve the most accurate cleaving and ideally prepare their fusion splicing.

Universal Single Holder Replaceable Ribbon Holder





Specifications	
Туре	Single & ribbon fiber cable cleaver
Cladding Diameter	125µm
Cleaved Length	Single fiber: 8~20mm / Ribbon fiber: 10mm
Applicable Fiber Cable	Single fiber: 250µm, 900µm, 3.0mm fiber cable and flat cable Ribbon fiber: 2 to 12 ribbon fiber cable
Typical Cleaved Angle	Less than 0.5 Degrees
Typical Blade Life Span	Total 48,000 fiber cleaves (1,000 fiber for 1 step * total 16 points * 3 heights)
Operation Steps	1 Steps
Reclaim Function	Blade pushback
Holder	Single: Universal holder Ribbon: Replaceable holder

### Size and Weight



Height 2.36 inches (60 mm) Width 3.74 inches (95 mm) Depth 2.99 inches (76 mm) Weight 0.62 pounds (282.5 grams)

#### Package



The information on this catalog is subject to change without prior notice.

You **dream,** We **DESIGN**  www.innoinstrument.com



Copyright © 2014 INNO Instrument Inc. All rights reserved. E-22F, 30, Songdomirae-ro, Yeonsu-gu, Incheon 406-840, Republic of Korea tel 82-32-837-5600 fax 82-32-837-5601

Printed in Korea