



MiniRAE 2000

Portable Handheld VOC Monitor

The rugged MiniRAE 2000 is the smallest pumped handheld volatile organic compound (VOC) monitor on the market. Its Photoionization Detector's (PID) extended range of 0 to 10,000 ppm makes it an ideal instrument for applications from environmental site surveying to HazMat/Homeland Security.

Key Features

- **Proven PID technology** The patented sensor provides a 3-second response up to 10,000 ppm and sets a new standard for resistance to moisture and dirt.
- **Wireless communication enabled and certified**
- **Self-cleaning lamp and sensor** The patented self-cleaning lamp and sensor minimize the need for maintenance and calibration.
- **The MiniRAE 2000 lamp and sensor can be taken apart in seconds for easy maintenance without tools!**
- **Measure more chemicals than with any other PID.** With over 100 Correction Factors built into the MiniRAE 2000 memory and the largest printed list of Correction Factors in the world (300+), RAE Systems offers the ability to accurately measure more ionizable chemicals than any other PID. When a gas is selected from the MiniRAE 2000's library, the alarm points are automatically loaded into the meter.
- **User friendly** screens make it easy to use for simple applications and flexible enough for sophisticated operations.
- **Drop-in battery** When work schedules require putting in more than the 10 hours supplied by the standard NiMH battery, the drop-in alkaline pack supplied with every MiniRAE 2000 lets you finish the job.
- **Rugged Rubber Boot** The standard rubber boot helps assure that the MiniRAE 2000 survives the bumps and knocks of tough field use.
- **Strong, built-in sample pump** draws up to 100 feet (30 m) horizontally or vertically.
- **Tough, flexible inlet probe**
- **Large keys** operable with 3 layers of gloves.
- **Easy-to-read display** with backlight.
- **Stores up to 267 hours of data** at one-minute intervals for downloading to PC.
- **3-year 10.6 eV lamp warranty**

Applications

HazMat/Homeland Security

- Initial PPE (personal protective equipment) assessment
- Leak detection
- Safety perimeter establishment and maintenance
- Spill delineation
- Decontamination
- Remediation

Industrial Hygiene/Safety

- Confined Space Entry (CSE)
- Indoor Air Quality (IAQ)
- Worker exposure studies

Environmental

- Soil and water headspace analysis
- Leaking underground storage tanks
- Perimeter fence line monitoring
- Fugitive emissions (EPA Method 21)
- Vapor recovery breakthrough
- Landfill monitoring



ver12_04.07

MiniRAE 2000

Specifications*

Detector Specifications

Size	8.2" L x 3.0" W x 2.0" H (21.8 x 7.62 x 5.0 cm)
Weight	20 oz with battery pack (553 g) w/o rubber boot
Sensor	Photoionization sensor with standard 10.6 eV or optional 9.8 eV or 11.7 eV UV lamp
Battery	• Rechargeable, external, field-replaceable Nickel-Metal-Hydride (NiMH) battery pack • Alkaline battery holder (for 4 AA batteries)
Operating Period	10 hours continuous operation
Display	Large LCD, backlight activated manually, by alarms or by darkness
Keypad	1 operation and 2 programming keys
Direct Readout	• VOCs as ppm by volume • High and low values • STEL and TWA (in hygiene mode) • Battery and shut down voltage
Alarms	90 dB buzzer and flashing red LED to indicate exceeded preset limits: • High: 3 beeps and flashes per second • Low: 2 beeps and flashes per second • STEL and TWA: 1 beep and flash per second • Alarms automatic reset or latching with manual override • Optional plug-in pen size vibration alarm • User adjustable alarm limits
Calibration	Two-point field calibration of zero and standard reference gas. Calibration memory of 8 calibration gases, alarm limits, span values and calibration date
Datalogging	267 hours (at one-minute intervals) with date/time. Header information includes monitor serial number, user ID, site ID, date and time
Sampling Pump	• Internal, integrated flow rate of 400 cc/min • Sample from 100' (30 m) horizontally or vertically
Low Flow Alarm	Auto shut-off pump at low flow condition
Communication	Download data and upload instrument set-up from PC through RS-232 link to serial port. Wireless communication enabled and certified (requires RAElink2 and ProRAE Remote to use)
Temperature	14° F to 104° F (-10° C to 40° C)
Humidity	0% to 95% relative humidity (non-condensing)
EM/RFI	Highly resistant to EMI /RFI. Compliant with EMC Directive 89/336/EEC
IP-rating	IP-55: protected against dust, protected against low-pressure jets of water from all directions
Hazardous Area Approval	• US and Canada: UL and cUL, Classified for use in Class I, Division 1, Groups A, B, C and D hazardous locations • Europe: ATEX II IG EEx ia IIC T4
Attachment	Durable bright yellow rubber boot w/belt clip & wrist strap
Warranty	Lifetime on non-consumable components (per RAE Systems Standard Warranty), 3 years for 10.6V PID lamp, 1 year for pump and battery

* Specifications are subject to change

** Performance based on isobutylene calibration

Default Sensor Settings**

Gas Monitor (ppm)	Range (ppm)	Resolution Time (T90)	Response
VOCs	0 to 99.9 ppm	0.1 ppm	< 3 sec
	100 to 10,000 ppm	1 ppm	< 3 sec

MiniRAE 2000 and Accessories

Monitor only includes:

- RAE Systems UV lamp: 10.6 eV, 9.8 eV or 11.7 eV as specified
- ProRAE Suite software package for Windows® 98, NT, 2000 and XP
- Computer interface cable
- 5-inch Flex-I-Probe
- External filter
- Rubber boot with belt clip
- Alkaline battery adapter
- Tool kit
- Lamp cleaning kit
- Nickel-Metal-Hydride (NiMH) battery
- 120/230 V AC/DC wall adapter (if specified)
- Operation and maintenance manual

Monitor with accessories kit adds:

- Hard transport case with pre-cut foam padding
- 5 porous metal filters and O-rings
- Organic vapor zeroing adapter
- Gas outlet port and tubing

Optional calibration kit adds:

- 10 ppm isobutylene calibration gas, 34L
- Calibration regulator and flow controller

Optional Guaranteed Cost of Ownership Program:

- 4-year repair and replacement guarantee
- Annual maintenance service

DISTRIBUTED BY:

ver12_04.07

RAE Systems Inc. USA/Canada 1-877-723-2878
3775 North First Street Europe/Russia +45 8652 5155
San Jose, CA 95134 USA Middle East/Australia 971 50 429 1385
raesales@raesystems.com China 8610 58858788
Asia +852 2669 0828

www.raesystems.com

