



MiniRAE 3000

Portable Handheld VOC Monitor



The MiniRAE 3000 is a comprehensive handheld VOC (Volatile Organic Compound) monitor that uses a third-generation patented PID technology to accurately measure more ionizable chemicals than any other device on the market. It provides full-range measurement from 0 to 15,000 ppm of VOCs.

The MiniRAE 3000 has a built-in wireless modem that allows real-time data connectivity with the ProRAE Guardian command center located up to 2 miles (3 km) away through a Bluetooth connection to a RAELink 3* portable modem.

KEY FEATURES

- Third-generation patented PID technology
- VOC detection range from 0 to 15,000 ppm
- 3-second response time
- Humidity compensation with built-in humidity and temperature sensors
- Six-month datalogging
- Large graphic display with integrated flashlight
- Multi-language support with 10 languages encoded
- IP-67 waterproof design

APPLICATIONS

- Oil and Gas
- HazMat
- Industrial Safety
- Civil Defense
- Environmental and Indoor Air Quality

- Highly accurate VOC measurements
- Patented PID sensor
- Low maintenance—easy access to lamp and sensor
- Low cost of ownership
- 3-year 10.6eV lamp warranty



Workers can quickly measure VOCs and wirelessly transmit data via Bluetooth.

*RAELink 3 modem is sold separately.



MiniRAE 3000

Portable Handheld VOC Monitor



SPECIFICATIONS

Instrument Specifications

Size	10" L x 3.0" W x 2.5" H (25.5 cm x 7.6 cm x 6.4 cm)
Weight	26 oz (738 g)
Sensors	Photoionization sensor with standard 10.6 eV or optional 9.8 eV or 11.7 eV lamp
Battery	<ul style="list-style-type: none">Rechargeable, external field-replaceable Lithium-Ion battery packAlkaline battery adapter
Running time	16 hours of operation (12 hours with alkaline battery adapter)
Display Graphic	4 lines, 28 x 43 mm, with LED backlight for enhanced display readability
Keypad	1 operation and 2 programming keys, 1 flashlight on/off
Direct Readout	Instantaneous reading <ul style="list-style-type: none">VOCs as ppm by volume (mg/m³)High valuesSTEL and TWABattery and shutdown voltageDate, time, temperature
Alarms	95dB at 12" (30 cm) buzzer and flashing red LED to indicate exceeded preset limits <ul style="list-style-type: none">High: 3 beeps and flashes per secondLow: 2 beeps and flashes per secondSTEL and TWA: 1 beep and flash per secondAlarms latching with manual override or automatic resetAdditional diagnostic alarm and display message for low battery and pump stall
EMC/RFI	Compliant with EMC directive (2004/108/EC) EMI and ESD test: 100MHz to 1GHz 30V/m, no alarm Contact: ±4kV Air: ±8kV, no alarm
IP Rating	<ul style="list-style-type: none">IP-67 unit off and without flexible probeIP-65 unit running
Datalogging	Standard 6 months at one-minute intervals
Calibration	Two-point or three-point calibration for zero and span. Calibration memory for 8 calibration gases, alarm limits, span values and calibration dates
Sampling Pump	<ul style="list-style-type: none">Internal, integrated flow rate at 500 cc/mnSample from 100' (30m) horizontally or vertically
Low Flow Alarm	Auto pump shutoff at low-flow condition
Communication	<ul style="list-style-type: none">Download data and upload instrument set-up from PC through charging cradle or optional Bluetooth™Wireless data transmission through built-in RF modem
Safety Certifications	US and Canada: CSA, Classified as Intrinsically Safe for use in Class I, Division 1 Groups A, B, C, D Europe: ATEX II 2G EEx ia IIC T4
Temperature	-4° to 122° F (-20° to 50° C)
Humidity	0% to 95% relative humidity (non-condensing)
Attachments	Durable bright yellow rubber boot
Warranty	3 years for 10.6 eV lamp, 1 year for pump, battery, sensor and instrument
Wireless Frequency	Bluetooth
Wireless Approvals	FCC Part 15, CE R&TTE, Others ¹
Radio Module	Supports BTM431

¹ Contact RAE Systems for country specific wireless approvals and certificates. Specifications are subject to change.

Sensor Specifications

Gas Monitor	Range	Resolution	Response Time T90
VOCs	0 to 999.9 ppm 1,000 to 15,000 ppm	0.1 ppm 1 ppm	< 3 s < 3 s

MONITOR ONLY INCLUDES:

- MiniRAE 3000 Monitor, Model PGM-7320
- Wireless communication module built in, as specified
- Datalogging with ProRAE Studio II Package
- Charging/download adapter
- RAE UV lamp, as specified
- Flex-I-Probe™
- External filter
- Rubber boot
- Alkaline battery adapter
- Lamp-cleaning kit
- Tool kit
- Operation CD-ROM
- Operation and Maintenance manual
- Soft leather case

OPTIONAL CALIBRATION KIT ADDS:

- 100 ppm isobutylene calibration gas, 34L
- Calibration regulator and flow controller

OPTIONAL GUARANTEED COST-OF-OWNERSHIP PROGRAM:

- 4-year repair and replacement guarantee
- Annual maintenance service

CORPORATE HEADQUARTERS

RAE Systems by Honeywell
3775 North First Street
San Jose, CA 95134 USA
RAE-InsideSales@honeywell.com

DS-1018-04

WORLDWIDE SALES OFFICES

USA/Canada 1.877.723.2878
Europe +800.333.222.44/+41.44.943.4380
Middle East +971.4.450.5852
China +86.10.5885.8788-3000
Asia Pacific +852.2669.0828

www.raesystems.com