

SUNRISE TELECOM®

SunSet MTT®

ACM II Chassis

Data Sheet



The SunSet MTT ACM II Chassis features a family of plug-in modules, providing a wide variety of testing capabilities for the Access Network

The Advanced Cable Maintenance (ACM II) Chassis, part of the SunSet Modular Test Toolkit (MTT) family of test sets, is a rugged, battery-operated test solution for installation and maintenance of physical layer access network services. The new SunSet MTT ACM II is the industry's premier handheld test system designed to qualify copper cables at VDSL2 frequencies, readying service providers for triple play deployments.

The ACM II covers an industry best frequency range from voiceband to 30 MHz – necessary for VDSL2 qualification based on FTTN or MDU architectures. Our patented 'detaptor' feature helps identify short bridge taps, which are especially harmful for VDSL2 transmission. In addition, ACM II offers key voice frequency features that are common to industry methods and procedures. Using the SunSet MTT ACM II enables service providers to complete installations in less time and with greater confidence in the quality of service delivered to customers.

KEY FEATURES

- Color display
- Easy-to-use interface
- Fast and easy one-button auto test
- Dual trace TDR for in-depth fault location
- RFL to locate resistance faults
- Spectrum analyzer - 30 MHz PSD background noise
- 30 MHz insertion loss
- Voice frequency features
 - Longitudinal balance
 - Circuit noise and power influence
 - Power harmonics analysis
- Detaptor (patented) to determine lengths of bridge taps
- Supports many SSMTT/SSxDSL test modules

BENEFITS

- Handheld and portable
- Flexible and dynamic
- Copper qualification with extended VDSL2 frequency range
- Standard POTS installation tests
- Convenient and cost-effective
- Integrated cable maintenance features
- Enhanced troubleshooting and repair
- Complete FTTn/x testing in one package

Advanced Cable Maintenance Features

TDR

Display Options

Single Trace

Dual Trace (Split Screen, Overlap, Difference, Recall)

Distance Range: Dependent on cable type and condition

English	
Cable Gauge	Distance Range
22 AWG	15 ft. to 24000 ft.
24 AWG	15 ft. to 18000 ft.
26 AWG	15 ft. to 12000 ft.

Metric	
Cable Gauge	Distance Range
0.6 mm	3 m to 7200 m
0.5 mm	3 m to 5400 m
0.4 mm	3 m to 3600 m

Display Resolution: 0.6% of selected range

Pulse Widths: 12 nS to 4 μ S, autoselect

Output Impedance: 100 Ω

Vp: 0.4 to 0.99 in 0.01 increments

Automatic search to first fault

RFL

Fault Range: 10 M Ω

RTS: 4 k Ω

Accuracy of RTF (at 1 M Ω)

$\pm 0.1\%$ RTS $\pm 0.1\Omega$ 0 Ω to 100 Ω

$\pm 0.2\%$ RTS $\pm 0.1\Omega$ > 100 Ω to 1000 Ω

$\pm 0.25\%$ RTS $\pm 0.1\Omega$ > 1000 Ω to 4000 Ω

DC Voltage

Range: 300V Max

Accuracy: $\pm 0.5\%$ ± 10 mV

AC Voltage

Detector: True RMS

Range: 250 VAC Max

Accuracy: $\pm 1\%$ ± 20 mV for 20 Hz to 1 kHz

Resistance

Range: 1 Ω to 100 M Ω

Accuracy

$\pm 1\%$ $\pm 1\Omega$ for 1 Ω to 1 M Ω

$\pm 2\%$ for > 1 M Ω to 4 M Ω

$\pm 5\%$ for > 4 M Ω to 100 M Ω

Capacitance

Range: 1 nF to 2 μ F

Accuracy

$\pm 2\%$ ± 300 pF for 1 nF to 1 μ F

$\pm 5\%$ for > 1 μ F to 2 μ F

Current

Load: 430 Ω

Range: 0 mA to 110 mA

Accuracy: $\pm 2\%$ ± 0.1 mA

Insertion Loss

Range: 0 to 80 dB

Accuracy: ± 2 dB

Frequency response sweep from 13 kHz to 30 MHz

Detaptor: Bridge Tap Detection (Patented)

WB Background Power Spectral Density (PSD) Noise

Frequency Range: 13 kHz to 30 MHz

Resolution Bandwidths: 4.3125 kHz, 34.5 kHz

Level Range: -30 to -140 dBm/Hz

VF Background Power Spectral Density (PSD) Noise

Frequency Range: Up to 6000 Hz

Level Range: 10 dBrn to 90 dBrn

Power Harmonics

Frequency Range: Up to 6000 Hz

Level Range: -50 dBm to 40 dBm

VF Metallic Noise

Range: 0 dBrn to 90 dBrn

Resolution: 1 dBrn

Accuracy

± 1.5 dB from 10 dBrn to 90 dBrn

± 2 dB from 0 dBrn to 10 dBrn

Filter: C-Message

Impedance: 600 Ω

Power Influence (Noise-to-Ground)

Range: 40 dBrn to 130 dBrn

Resolution: 1 dBrn

Accuracy: ± 1.5 dB

Filter: C-Message

Longitudinal Balance

Frequency: 1 kHz

Range: 0 to 70 dB

Accuracy: ± 2 dB

Impulse Noise

Threshold Range: 50 dBrn to 100 dBrn

Dead Time Range: 100 μ S to 255 mS

Max Count Range: 1 to 9999

Timer: Settable from 1 to 999 minutes or continuous

Signal-to-noise

Frequency range: 13 kHz to 30 MHz

Near End and Far End Crosstalk (NEXT/FEXT)

Frequency range: 34.5 kHz to 30 MHz

Auto Test

User selectable tests with CSV output

Reports PASS/FAIL/MARGINAL status where applicable

Load Coil Detector

Graphic and count

Cable Pair Detect

Audible connectivity verification

Transmitter

Frequency Range: 10 kHz to 30 MHz
Frequency Resolution: 0.1 kHz
Frequency Accuracy: ± 25 ppm
Levels: 0 to -40 dBm in 1 dB steps
Level Accuracy: ± 1 dB
Output Impedance: 100 Ω balanced

Receiver

Measurement Method: FFT
Frequency Range: 13 kHz to 30 MHz
Frequency Resolution: 4.3125 kHz
Level Range
+5 to -80 dBm for 13 kHz to 18 kHz
+10 to -80 dBm for > 18 kHz to 30 MHz
Level Resolution: 0.1 dB
Level Accuracy: ± 1 dB
Input Impedance: 100 Ω balanced

PRODUCT DESCRIPTION

Size (W \times L \times H): 4.1 \times 10.6 \times 2.6 in (10.5 \times 27 \times 6.5 cm)
Weight: 3.5 lb (1.6 kg)
Display: Backlit 240 \times 320 dot STN indoor/outdoor Color screen;
CFL Backlight
Connectors: Five 2 mm banana test leads
LEDs: 20 bi-color
Serial Port: 8-DIN, RS-232C (V.24) DTE
DC Power Jack
Battery: Rechargeable, field replaceable NiMH pack
Charger: Universal 100-240 VAC adapter with IEC connector
Operating Temperature: 23° to 113°F (-5° to 45°C)
Storage Temperature: -4° to 158°F (-20° to 70°C)
Humidity: 5% to 85% noncondensing

ORDERING INFORMATION

SSMTT-ACM2

SunSet MTT ACM II

Includes a high resolution color display, mini-banana interface, and the following standard features: Dual and single trace TDR, DMM, Load Coil Detector, Metallic Noise, Power Influence, Longitudinal Balance, Cable Pair Detect, and Impulse Noise. Also includes standard 2.2 MHz measurement range for the following features: Insertion Loss, PSD Background Noise, Signal to Noise, and Frequency Generator. Standard Accessories include test cables, SunSet Jacket, and Certificate of Calibration.

SWMTT-ACM2-VDSL

Extended VDSL Range Features for SunSet MTT ACM II
Includes extended VDSL measurement range for the following features: Insertion Loss, PSD Background Noise, Signal to Noise, and Frequency Generator. Also adds NEXT and FEXT features.

SWMTT-ACM2-RFL

RFL Features for SunSet MTT ACM II
Includes Resistance Fault Locate features for the SunSet MTT ACM II

Replacement Accessories

SA274	Cable, 2 mm Test Leads (Black/Red) with bed-of-nails alligator clips, 6'
SA275	Cable, 2 mm Test Lead (Green) with bed-of-nails alligator clips, 6'
SA276	Cable, 2 mm Test Leads (Yellow/Blue) with bed-of-nails alligator clips, 6'
SA277	Cable, 2 mm Test Leads Kit (set of five cables)
SA278	Cable, RFL Strap
SA601	Jacket, SunSet MTT Family

For more information or a directory of sales offices: info@sunrisetelecom.com | www.sunrisetelecom.com